



Introducing the DPI620 HART® Communicator

Big HART in a small package
for a small price.



Item	Value	Units
Device setup		
PV	0.0006	bar
PV AO	-4.001	mA
PV LRV	0.000	bar
PV URV	7.000	bar

DPI620 – the latest in HART COMMUNICATORS

- ✓ Colour interface
- ✓ Touch screen operation
- ✓ Retains **COMPLETE** device descriptor (DD) library
- ✓ Free DD library upgrades
- ✓ Robust, weatherproof and compact

and more ...

CH2	Current (24V)	24V
	4.0017	
	55.0000	mA
HART	10.0000 17.0000	
	0.0000	bar

- ✓ 24V loop power for energizing HART devices
- ✓ Built-in selectable 250 ohm loop resistor
- ✓ Measure the mA output and compare against digital HART mA value, **ALL ON ONE SCREEN**
- ✓ Simultaneously **MEASURE** and **SOURCE** the primary variable – **NO SECONDARY CALIBRATOR REQUIRED**

DPI620 Advanced Modular Calibration System —pressure measurement and generation in one compact device.



- Pressure accuracy from 0.025%
- Interchangeable pressure modules from 10 inH₂O to 15,000 psi
- Pressure generation from vacuum to 1,500 psi pneumatic or 0 to 15,000 psi hydraulic
- Quick-fit connections with no need for tools
- Overpressure protection

The DPI620 is a HART COMMUNICATOR and CALIBRATOR all in one handheld package, saving about \$5,000. CALL FOR SPECIAL PRICING AND CURRENT TRADEIN OFFERS.

1-877-844-6665 x225