Procon Systems Migration Option for RigRat III Transportable Gas Detector

Effective December 31, 2017. Honeywell (aka BW by Honeywell) is no longer taking orders for the RigRat III Electronic Controller.

In an effort to meet our customers' requirements, we have looked for the closest replacement product available.

The Procon Systems R4S is this best fit

This information sheet provides comparison of these two sets of specifications.



Common Sensors (others available)

LEL (combustible)	Catalytic Bead
O2 (oxygen)	Electrochemical
H2S (hydrogen sulfide)	Electrochemical
CO (carbon monoxide)	Electrochemical
NH3 (ammonia)	Electrochemical
Cl2 (chlorine)	Electrochemical
SO2 (sulfur dioxide)	Electrochemical
C6H6 (benzene)	PID (10.6eV)
CH4 (methane)	Infrared
HC (hydrocarbons)	Infrared

	Yes
	Yes
	Yes
	Yes
	Yes
Yes	
Yes	
Yes	No
Yes	No
Yes	No

Alarm Settings

Alarm Set Points Activate on Increase/Decrease Latching/Non-Latching

3 configurable + fault	1 for external alarms	
Y	es	
Yes		

Summary Specifications

Dimensions Weight

Cable Length

Federal Signal 302GCX Audible Alarm

580,000 candela Blue Strobe Light Visual Alarm

Gas Sensor Ports Enclosure Rating

Controls

Operating Voltage

Display

Warranty

Height: 62", Width 16", Depth 17"	Height: 62", Width 18", Depth 13"	
42 lbs	52 lbs	
Up to 100' (30 m)		
Yes		
Yes		
4	2	
NEMA 4x Class 1 Div 2 (C,D)	NEMA 4x Class 1 Div 2 (C,D)	
Magnet used for menu functions. Calibrate without opening the enclosure. External power switch.	Internal push buttons for menu functions. Must open to calibrate. Internal power switch.	
120VAC with full batt backup	120VAC with partial batt backup	
Alphanumeric LCD display with backlighting. 2 lines for gas and concentration readout, plus userfriendly calibration and setup	Custom LCD, no backlight	
2 years parts and labor		